


KIWI 1910 3D



Capacity Gross / Net (L)	1851 L / 1630 L
Outer Dimensions (WxDxH) mm	1910 x 780 x 2082
Internal Dimensions (WxDxH) mm	1824 X 636 X 1594
Temperature Range (°C)	+1°C/+7°C
Refrigerant / Voltage / Frequency	R290 / 220-240 V / 50 Hz
Thermostat	Digital
Glass	Double tempered + LOW-E + ARGON
Door Frame	FRAMELESS -full glass/aluminium sides
Int. & Ext. Body	Galvanised 0,5mm sheet metal
Cooling System	Ventilated
Evaporator Type	Fin Type
Condenser Type	Dust Free /Maintenance free
Lightening	LED horizontal & Vertical + on/off switch
Self Closing Door	Yes
Insulation	43 mm
Shelves	4+4+4 / PE coated + price holder
Adjustable Feet / Roller	4x adjustable feet + 6x Roller
20DC/40DC-HC/Truck	9 / 18 / 20



KIWI 1910 3D 3M2



Options

3321 kWh/annum

- Door lock
- Branding
- Castor
- Automatic defrost
- Lightening from door


2.49 m³

 **7°C**
-1°C

Inner Body	Outer Body	Outer Body	Outer Body
RAL 9002	RAL 9002	RAL 9005	RAL 7016
STANDARD	STANDARD	OPTIONAL	OPTIONAL