


KIWI PREMIUM 1620 2D



Capacity Gross / Net (L)	1555 L / 1432 L
Outer Dimensions (WxDxH) mm	1620 X 792 X 2082
Internal Dimensions (WxDxH) mm	1534 X 636 X 1594
Temperature Range (°C)	+1°C/+7°C
Refrigerant / Voltage / Frequency	R290 / 220-240 V / 50 Hz
Thermostat	Digital
Glass	Double tempered + LOW-E + ARGON
Door Frame	FRAMELESS -full glass/aluminium sides
Int. & Ext. Body	Galvanised 0,5mm sheet metal
Cooling System	Ventilated
Evaporator Type	Fin Type
Condenser Type	Dust Free /Maintenance free
Lightening	LED horizontal & Vertical + on/off switch
Self Closing Door	Yes
Insulation	43 mm
Shelves	4+4 / PE coated + price holder
Adjustable Feet / Roller	3x adjustable feet + 6x Roller
20DC/40DC-HC/Truck	10 / 21 / 24



Options

- Door lock
- Branding
- Castor
- Lightening from door
- Automatic defrost
- Lightened front grill



KIWI PREMIUM 1620_2D



2555 kWh/annum


2.22 m³


7°C
-1°C

Inner Body	Outer Body	Inner Body	Outer Body
RAL 9005	RAL 9005	RAL 9002	RAL 7042
STANDARD	STANDARD	OPTIONAL	OPTIONAL